



装配例		型式例													
		截面图	材料	温度范围	速度	特点	代号								
			NBR FKM PU	-30至100 -20至200 -35至100	2	有容沟槽，安装方便，有密封和防尘两个唇口	F4								
		尺寸	公差												
$\phi D2$	H10														
$\phi D1$	H10														
L1	+0.15,0														
		L2=L3+2													
d1	D1	L3	H	d1	D1	L3	H	d1	D1	L3	H	d1	D1	L3	H
10	18	6	8	45	53	6	8	110	122	8.2	11	210	225	9.5	13
12	20	6	8	46	54	6	8	115	127	8.2	11	220	235	9.5	13
14	22	6	8	48	56	6	8	120	132	8.2	11	225	240	9.5	13
15	23	6	8	50	58	6	8	125	137	8.2	11	240	255	9.5	13
16	24	6	8	52	60	6	8	130	142	8.2	11	250	265	9.5	13
18	26	6	8	55	63	6	8	135	147	8.2	11	260	275	9.5	13
20	28	6	8	56	64	6	8	140	152	8.2	11	275	290	9.5	13
22	30	6	8	60	68	6	8	145	157	8.2	11	280	295	9.5	13
24	32	6	8	63	71	6	8	150	162	8.2	11	290	305	9.5	13
25	33	6	8	65	73	6	8	155	167	8.2	11	300	315	9.5	13
28	36	6	8	68	76	6	8	160	172	8.2	11	310	325	9.5	13
30	38	6	8	70	78	6	8	165	177	8.2	11	320	335	9.5	13
32	40	6	8	75	83	6	8	170	182	8.2	11	350	365	9.5	13
35	43	6	8	80	88	6	8	180	192	8.2	11	360	375	9.5	13
36	44	6	8	85	93	6	8	185	197	8.2	11	370	385	9.5	13
37	45	6	8	90	98	6	8	190	202	8.2	11	400	415	9.5	13
38	46	6	8	95	103	6	8	195	207	8.2	11	440	455	9.5	13
40	48	6	8	100	108	6	8	200	212	8.2	11				
42	50	6	8	105	117	8.2	11	205	220	9.5	13				